

BOX BULLET CAMERA

CJ-9511DIR

HD



1.3 Megapixel



SPECIFICATION

Model	CJ-9511DIR
Camera	
Image Sensor	1/3"CMOS
Image Size	1280 x 960
Electronic Shutter	1/25s ~ 1/100000s
Min. Illumination	0LUX(IR LED ON)
Lens	6mm(4mm,8mm optional)
Lens Mount	M12
Wide Dynamic Range	Digital WDR
Digital NR	3D DNR
Image	
Video Compression	H.264
Resolution	960P(1280x960), 720P(1280x720), VGA(640x480), QVGA(320x240)
Multi-stream	1280 x 960(1~30fps) / 1280x720(1~ 30fps) 1280x720(1 ~10fps) / 640x480(1 ~ 30fps) / 320x240(1 ~30fps)
Bit rate	64Kbps ~ 4Mbps
Encode Mode	VBR/CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	Saturation, Brightness, Contrast, etc. adjustable through client software or web browser
Audio Compression	G711A
Interfaces	
Network	RJ45
Audio	One-way audio(MIC IN x1)
Functions	
Remote Monitoring	IE browsing,CMS remote control
Online Connection	Support simultaneous monitoring for up to 4 users ; Support multi-stream real time transmission
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,FTP
Storage	Network remote storage
Smart Alarm	Motion Alarm
Day&Night	ICR
PoE	Yes
IR Distance	20-30m
Water-proof	IP66

Others	
Power Supply	DC12V/POE
Operating Environment	-40 ℃-50 ℃,10% ~90% humidity
Dimensions	Φ87mm x 219mm
Weight (net)	635g

DIMENSION

