



CJ Combine Co.,Ltd.
 65/31 โครงการพีเมียมเพลส รามอินทรา14
 แขวงท่าแร้ง เขตบางเขน กรุงเทพฯ 10230
 โทร. 0-2943-5779 , 0-2943-5854-5 แฟกซ์. 0-2943-7913
 E-Mail : cjcombine@gmail.com

CJ-5516

AHD DVR

SPECIFICATION

Operating System		Embedded Linux
Collection standards	Video Standard	AHD
Interface	Video Input	16ch 720P
	Video Output	1ch VGA, 1ch HDMI Supports simultaneous output
	Spot	No
	Audio Input	2ch (Up to 6ch)
	Audio Output	1ch
	Alarm Input	None (Up to 4ch)
	Alarm Output	1ch
	Net Interface	RJ45 10M/100M
	485 Interface	1
	232 Interface	0
	USB Interface	2 USB ports(USB2.0)
	eSATA	No
Operation	GUI	GUI
	Mouse	Left and right buttons, scroll wheel operation
	Front Plank	Without SCM
	remote controller	Support
Monitoring (preview)	Split Screen Mode	1/4/8/9/16 screen
	TV(Monitor)	Not supported
	VGA	1920*1080, 1280*720,1440*900,1280*1024, 1024*768, 800*600
Video Codec	HDMI	1920*1080, 1280*720,1440*900,1280*1024, 1024*768, 800*600
	Compression Format	H.264(High Profile)
	Resolution	Main stream: 720P/D1 Secondary stream: D1 (12)/CIF/QCIF
	Compression	16*720p
	Decoding	4*720p
	Capture	No
Audio	HVR/NVR mode	Support
	Compression	Support
	Decoding	Support
Record & Playback	Voice Intercom	Support
	Record Mode	Manual>Alarm>Video Detection>Timing
	Local Playback	16 channels
Storage & Backup	Record Search	Time, event, channel
	Record Storage	Hard disk x2 SATA ports (each max to 4TB) and network
Alarm	Backup Mode	Network /U disk/ USB mobile hard disk/ USB recorder
	Intelligent detection	No
	Motion Detection	Supports multi-level sensitivity
	Video block	Support
	Video loss	Support
External alarm	Support	

